

## PCR / Gradient PCR Touch Screen



This series product adopts 8 pieces custom-made US Marlow peltier, Max. ramping rate 5°C, cycle times > 600000. More advanced technologies applied on the product: Windows operating system; color touch-screen; double blocks can run independently; replaceable block; control by PC function; print function; extra large data storage and USB interfaces. All the above functions make it demand high need experiments.

**Key Features :** 1). Each thermal block has 4 independent temperature control sensors and 8 peltier heating units to ensure accurate and uniform temperature across block surface, and provide users with replicating previous condition set-up.  
2). 8" TFT color touch-screen with graphical display provides easy use for setting up and monitoring.  
3). The actual and target temperatures can be viewed and displayed graphically in real time.  
4). Built-in 11 standard program file template, can quickly edit the required files.  
5). Internal flash memory for 10000 typical PCR files in free configurable folders. 6). Automatic restart after power failure.

<b>Model</b>	<b>GE3961T/3602T/3483T/3384T</b> General	<b>GE3961G/3602G/3483G/3384G</b> Gradient
Capacity	96×0.2ml , 60×0.5ml , Double 48×0.2ml , 48×0.2ml+30×0.5ml,384well , In-situ Plate	
Temperature Range	0~100°C	
Max. Heating Rate	5°C/s	
Max. Cooling Rate	4°C/s	
Uniformity	≤±0.2°C	
Accuracy	≤±0.1°C	
Display Resolution	0.1°C	
Temperature Control	Block\Tube	
Ramping Rate Adjustable	0.1~5°C	
Gradient Uniformity	/	≤±0.2°C
Gradient Accuracy	/	≤±0.2°C
Gradient Temp. Range	/	30~100°C
Gradient Spread	/	1~30°C
Hot Lid Temperature	30~110°C	
Hot Lid Height Adjustable	Stepless Adjustable	
Number of Programs	10000 +(USB FLASH)	
Max. No. of Step	30	
Max. No. of Cycle	99	
Time Increment/Decrement	1 Sec ~ 9 Min 59 Sec	
Temp. Increment/Decrement	0.1~9.9°C	
Pause Function	Yes	
Auto Data Protection	Yes	
Hold at 4°C	Forever	
Print	Yes	
LAN to computer	Yes	
LCD	8inch, 800×600 Pixels, TFT	
Communication	USB2.0 , LAN	
Dimensions	380mm×240mm×260mm (L×W×H)	
Weight	8.5kg	
Power Supply	85~264VAC , 47~63Hz , 600W	